

# We test, You produce.

## F5200

### TOUCH SCREEN COMPACT LEAK TESTER

The ATEQ F5200 in its compact format is the easiest leak detector to operate and integrate into manufacturing operations. Its comprehensive specifications, including ATEQ's latest developments in pressure decay technology, make it an extremely versatile instrument.

The F5200 offers a touchscreen graphical interface to combine great functionality and ease of use with intuitive menu-driven operator controls.

#### Highlights

- COLOR TOUCHSCREEN
- MAXIMUM PERFORMANCE
- ADVANCED TECHNOLOGY



#### Applications



##### **AUTOMOTIVE**

shock absorbers, gearboxes, tank caps, carburetors, non return valves, cylinder heads, filters, radiators, seals, cylinders, engine oil and water circuits...



##### **DOMESTIC APPLIANCES**

bottles, percolators, cookers, steam irons, ovens, washing machines...



##### **MEDICAL**

catheters, dialysis equipment, micropipettes, plastic taps, drain bags, syringes, valves...



##### **PACKAGING**

aerosol cans and valves, trigger pumps, ink cartridges, cosmetic bottles, food sachets...



# F5200

## TOUCH SCREEN COMPACT LEAK TESTER

### Measurement Ranges

TEST PRESSURE MEASUREMENT		
Range	Accuracy	Maximum resolution
F.S. = 75 mbar*	+ (1.5% of the P + 0.2 hPa)	0.1% of the full scale
F.S. < 0.3 bar	± (1.5% of the P + 1 hPa)	
0.3 < F.S. < 1 bar	± (1.5% of the P + 3 hPa)	
1 < F.S. < 5 bar	± (1.5% of the P + 7.5 hPa)	
5 < F.S. < 10 bar	± (1.5% of the P + 15 hPa)	
10 < F.S. < 20 bar	± (1.5% of the P + 30 hPa)	
PRESSURE DROP MEASUREMENT		
Range	Accuracy	Maximum resolution
0 - 50 Pa	± (2% of the P + 0.5 Pa)	0.01 Pa
0 - 500 Pa	± (2.5% of the P + 1 Pa)	0.1 Pa
0 - 5000 Pa	± (2.5% of the P + 10 Pa)	1 Pa
ELECTRONIC PRESSURE REGULATION (1 or 2) Vaccum / 1-10 kPa / 5-50 kPa / 20-200 kPa / 50-500 kPa / 100-1000 kPa / 100-1600 kPa / 100-2000 kPa		

\* Specific (relative) : F.S. = Full Scale : P = Pressure

### Main Features

- Differential pressure decay leak measurement
- Large ranges of leak measurement ( $\Delta P$ ) F.S. : 50 Pa, 500 Pa or 5000 Pa
- 32 programs
- Set-up on-line (via USB port)
- 2 languages (English + one other)
- Manual calibration on front panel with calibrated leak
- ROHS standard

### Test Modes

- $\Delta P$  (Pa, 1/10 Pa)
- $\Delta P / \Delta t$  (Pa/s, 1/10 Pa/s)
- Flow units (mm<sup>3</sup>/s, cm<sup>3</sup>/s, cm<sup>3</sup>/min, cm<sup>3</sup>/h)
- Blockage test
- and others, depending on your applications

### Flexible Communication Format

- RS232: printer / Bar code reader
- Slave USB: supervision
- Master USB: USB key to transfer (parameters, results, curves, statistics)
- Ethernet: email alert/ Modbus IP
- Option: profibus, devicenet



# ATEQ

### Technical Specifications

<b>Physical</b>	Weight: 4 Kg Dimensions: (WxHxD) 250x136x367 mm
<b>Interface</b>	Graphic touchscreen with simple intuitive menu-driven operator controls
<b>Electrical Supply</b>	90 - 260 V AC / 1.6 A
<b>Air Supply</b>	Clean and dry air required Air quality standard to be applied (ISO 8573-1)
<b>Temperature</b>	Operating: + 0°C to + 45°C Storage: 0°C to + 60°C

### Options

- 7 inputs / 5 outputs
- Electronic regulator
- Dual pressure
- Automatic calibration check
- 2 pneumatic outputs for control of sealing connectors
- 6 x 24 V programmable outputs for external automation

### Accessories

- Remote Control
- Y valve
- Ateq software (WinAteq)
- Leak-Flow calibrator
- Connectors



PRESSURE CALIBRATOR



CONNECTORS